

Granville Red Rubber Grease

70g Tube & 500g Tin

PRODUCT DESCRIPTION

Granville Red Rubber Grease has been specifically designed for use in environments where compatibility with seals and/or resistance to Hydrocarbons is required. Red Rubber Grease is compatible with both natural rubber and synthetic seals. The formulation of the grease makes the product mechanically stable and resistant to mineral oils and most hydrocarbons, including many solvents.

PRODUCT BENEFITS

- * Mineral oil free
- * Mechanically stable
- * Resistant to hydrocarbon solvents
- * Good operating temperature range

PRODUCT USAGE

Granville Red Rubber Grease is ideal for lubrication of valves, slides, taps and brake components operating in the presence of hydrocarbon solvents and also for most general lubricant duties where there is concern over compatibility with seals. Is suitable for certain types of brake assemblies which require this type of grease.

DIRECTIONS FOR USE

Apply grease to the area required ensuring the area is free from contamination and residue.

STORAGE INSTRUCTIONS

Store sealed in a cool, dry place.

SHELF LIFE

3 years from date of manufacture.



* Image for illustrative purposes only.

SIZE	PART NO	BARCODE
70g Tube	0847	5020618008477
500g Tin	0846	5020618008460



Granville Red Rubber Grease

70g Tube & 500g Tin

SPECIFICATION INFORMATION

Operating Temperature: -20°C to +120°C

NLGI Classification: 2-3

Worked Penetration: 245-275

Appearance	: Smooth red grease
Odour	: Characteristic
Solubility	: Insoluble in water
Flammability	: Infusible

SAFETY PRECAUTIONS

Please see our latest EC Safety Data Sheets for details.

TRANSPORT CLASSIFICATION

Please see our latest EC Safety Data Sheets for details.

